


Propyl acetate**NO.145****Performance**

Measuring Range	20 to 500 ppm
Number of Pump Strokes	2
Correction Factor	1
Sampling Time	4 minutes per pump stroke
Detecting Limit	4 ppm (n=2)
Color Change	Yellow → Blackish brown → Pale blue after few minutes
Reaction Principle	Propyl acetate reduces chromic acid to produce blackish brown.
Coefficient of Variation	15% (for 20 to 100 ppm), 10% (for 100 to 500 ppm)
Shelf Life	2 Years
Corrections for temperature & humidity	Temperature correction is necessary
Store the tubes at cool and dark place.	

Possible coexisting substances and their interferences (NOTE)

Substance	Concentration	Interference	Change color by itself
Alcohols	-	Plus error	Produce blackish brown then turns to pale blue
Ketones	-	Plus error	Produce blackish brown then turns to pale blue
Esters	-	Plus error	Produce blackish brown then turns to pale blue

Calibration gas generation Diffusion tube method

TLV-TWA	TLV-STEL	Explosive range
200ppm	250ppm	1.7 to 8%

Nextteq LLC – 8406 Benjamin Rd., Suite J, Tampa FL 33634, USA

Phone (toll free): 877-312-2333 Fax (toll free) 877-312-2444

[Policy Statement](#) and [Legal Notices](#)

Nextteq is Gastec's Exclusive U.S. Master Wholesale Distributor. Gastec tubes and pumps are manufactured by the Gastec Corporation.