



Performance The minimum scale value (10ppm) is not printed on the tube, but only the scale line is printed.

Measuring range	5 to 10 ppm	(10) to 250 ppm	250 to 625 ppm
Number of pump strokes	2 (200 ml)	1 (100 ml)	1/2 (50 ml)
Correction factor	1/2	1	2.5
Sampling time	3 min	1.5 min	1 min

Detecting limit : 1 ppm (2 pump strokes)
 Colour change : White → Brown
 Corrections for temperature & humidity : Unnecessary
 Relative standard deviation : 10 % (for 10 to 50 ppm) , 5 % (for 50 to 250 ppm)
 Shelf life : 3 years

Reaction principle



Possible coexisting substances and their interferences

Substance	Concentration	Interference	Changes colour by itself to
Toluene	$\geq 1/5$	+	Brown
Acetylene, Hexane	≤ 2000 ppm	No (Two layers)	} Pale brown (Whole layer)
Carbon monoxide	≤ 1000 ppm	No (Two layers)	
Benzene	$\geq 1/5$	+	Pale yellow

Other substance measurable with this detector tube

Substance	Correction	No. of pump strokes	Measuring range
Trimethylbenzene	by scale	2	10 to 300 ppm

Calibration gas generation

Diffusion tube method